

Remote Modules
WIFI I/O Remote Modules
Palm-WIFI Series(WIFI Remote Modules)

TYPE	P-WIFI69
	Digital Output Module
Operation Voltage	10~30VDC/24VAC
Digital input(Isolation)	

Digital Output(Isolation)	8*(Power Relay)
Continuous Current	250VAC(5A)/30VDC(5A)
Analog Inputs	---
Analog Input Type	---
Communication Baud Rate	2400~921600bps
Digital Input&Output Isolation	YES(5000VDC)
Input Operating Frequency	10HZ
Output Operating Frequency	Transistor:10HZ
Operation Temperature	-20 to +75 °C
Degree Of Protection	IP20
Installation	35 mm DIN rail or Flush mounting
Dimension (W x H x D)	76*118*38 mm
Analog Inputs	4*(16-bit)
Analog Input Type	2* 0/4~20mA 2* PT-100/1000 (-200 ~ +600°C)
Analog Outputs	2*(12-bit)
Analog Output Type	0/4 ~20mA
Input Impedance	Current: 100 Ω RTD : 10 M Ω
Analog Input / Output Accuracy	$\pm 0.1\%$ / $\pm 1\%$
Interface	WIFI + RS-485
Channel Independent Configuration	YES
Sampling Rate	10 sample/second (total)
CMR @ 50/60 Hz	120 dB
Span Drift	± 50 ppm/°C
Zero Drift	$\pm 18 \mu$ V/°C